

Technical Specifications -Star Rated Window AC (With R-22 Refrigerant)

Model Name	Model No.	Tonnage Class	Star Rating	Rated Cooling / (Heating) Capacity (BTU/Hr)	Rated Cooling/(Heating) Capacity (W)	Rated Power Input Cooling/ (Heating) (W)	Rated EER Cooling/(Heating) (W/W)	Air Flow Cooling/(Heating) (CFM)	Sound Level Cooling/(Heating) (dB)*	Dimension (WXHxD)(mm)	Net Weight (Kg)
SUMMER TM	RAT518HUD	1.5	5	18300	5350	1575	3.40	500	46	660X430X805	66
SUMMER QC	RAV513HUD	1.1	5	13307	3900	1165	3.35	420	45	660X430X805	55
	RAV518HUD	1.5	5	18300	5350	1530	3.50	500	45	660X430X805	63
	RAV222HUD	2.0	2	21020	6160	2200	2.80	500	48	660X430X805	64
KAZE PLUS	RAW511KUD	1.0	5	11942	3500	1030	3.40	400	50	660X430X755	52
	RAW312KWD	1.0	3	12000	3516	1190	2.95	300	50	560X377X615	43
	RAW518KUDZ1	1.5	5	18000	5275	1575	3.35	450	50	660X430X755	63
	RAW318KUD	1.5	3	17402	5100	1650	3.09	450	50	660X430X755	61
	RAW218KUD	1.5	2	17402	5100	1785	2.86	450	50	660X430X755	61
	RAW222KVD	2.0	2	21019	6160	2240	2.75	470	52	660 X 430 X 755	64
KAZE REIDAN	RAW018KTH	1.5	#Not Applicable	18000/(17300)	5275/(5069)	1775/(1755)	2.97/(2.89)	420/(420)	50/(50)	660X430X755	62

*At Super silent fan speed & at a distance of 1 m .

Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C.

Due to continuous research & development , specifications, features & model colour may change without prior notice .

Some of the models may not be available at all the Hitachi outlets.

#BEE star rating scheme does not cover testing of these models.