

TECHNICAL SPECIFICATIONS

LOGICCOOL 5200f

DESCRIPTION	UNIT			
TONNAGE CLASS		1.0TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	5	4
Unit	Model Number	RAU512KWDB	RAU518KUDB	RAU423KWDB
IDU	Model Number	RAS512KWDB	RAS518KUDB	RAS423KWDB
ODU	Model Number	RAC512KWDB	RAC518KUDB	RAC423KWDB
Compressor	Type	ROTARY	ROTARY	ROTARY
Refrigerant	Type	R-22	R-22	R-22
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	12000	18562	23203
Rated Cooling Capacity	Watts	3516	5440	6800
Rated Power Input	Watts	977	1495	2000
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.60	3.64	3.40
Current Drawn	Amps	4.3	6.6	8.9
Fan Speed	Steps	3	3	3
Air Flow (IDU) (Cooling -Super High)	CFM	425	545	636
Sound Level* (IDU)	dB	36	37	40
Dimension (IDU) (W X H X D)	mm	798 X 295 X 239	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	9.5	12.9	12.9
Net Weight (ODU)	Kg	31.0	38	44.9
Remocon	Type	WIRELESS	WIRELESS	WIRELESS

Features may vary from model to model, some of the models may not be available at all Hitachi outlets. *At Super silent fan speed & at a distance of 1mtr., Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. T&C Apply: Products shown in catalogue are for representation purpose only. Due to continuous research and development, specifications, features and model colour may change without any prior notice.