

TECHNICAL SPECIFICATIONS		Zunoh 5200f			
DESCRIPTION	UNIT				
Tonnage Class		1.2TR	1.5TR	1.8TR	2.0TR
Star Rating	No of BEE Stars	5	5	5	5
Unit	Model Number	RAU514AWD	RAU518AVD	RAU522AWD	RAU524AVD
IDU	Model Number	RAS514AWD	RAS518AVD	RAS522AWD	RAS524AVD
ODU	Model Number	RAC514AWD	RAC518AVD	RAC522AWD	RAC524AVD
Compressor	Type	ROTARY	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity / Heating Capacity	BTU/Hr	13819	18800	22000	24000
Rated Cooling Capacity / Heating Capacity	Watts	4050	5500	6445	7030
Rated Power Cooling Input / Heating	Watts	1065	1485	1835	1950
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.80	3.70	3.51	3.61
Current Drawn Cooling / Heating	Amps	4.7	6.6	8.2	8.6
Fan Speed	Steps	5	5	5	5
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	450	600	670	670
Sound Level* (IDU) Cooling / Heating	dB	34	33	37	37
Dimension (IDU) (W X H X D)	mm	798 X 295 X 245	997 X 294 X 258	997 X 294 X 258	997 X 294 X 258
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299	792 X 600 X 299
Net Weight (IDU)	Kg	9.5	13	13	13.9
Net Weight (ODU)	Kg	38.2	41.0	48.3	48.1
Remocon	Type	Wireless	Wireless	Wireless	Wireless
Connecting Kit	inch	1/2" & 1/4"	5/8" & 1/4"	5/8" & 1/4"	5/8" & 1/4"

Features may vary from model to model. \*At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52° C. Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.