

TECHNICAL SPECIFICATIONS		Toushi 5200f		
DESCRIPTION	UNIT			
Tonnage Class		1.0TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	5	4
Unit	Model Number	RAU512KWD	RAU518KWD	RAU423KWD
IDU	Model Number	RAS512KWD	RAS518KWD	RAS423KWD
ODU	Model Number	RAC512KWD	RAC518KWD	RAC423KWD
Compressor	Type	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity / Heating Capacity	BTU/Hr	12000	18562	23203
Rated Cooling Capacity / Heating Capacity	Watts	3516	5440	6800
Rated Power Cooling Input / Heating	Watts	977	1495	2000
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.60	3.64	3.40
Current Drawn Cooling / Heating	Amps	4.3	6.6	8.9
Fan Speed	Steps	3	3	3
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	425	545	636
Sound Level* (IDU) Cooling / Heating	dB	36	37	40
Dimension (IDU) (W X H X D)	mm	798 X 295 X 239	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	9.5	12.9	12.9
Net Weight (ODU)	Kg	31.0	38	46.8
Remocon	Type	Wireless	Wireless	Wireless
Connecting Kit	inch	1/2" & 1/4"	5/8" & 1/4"	5/8" & 1/4"

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52° C. Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.