

TECHNICAL SPECIFICATIONS		Toushi 3200f			
DESCRIPTION	UNIT				
Tonnage Class		1.0TR	1.5TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	3	3	3	3
Unit	Model Number	RAU312KWD	RAU317KWD	RAU318KWD	RAU323KWD
IDU	Model Number	RAS312KWD	RAS317KWD	RAS318KWD	RAS323KWD
ODU	Model Number	RAC312KWD	RAC317KWD	RAC318KWD	RAC323KWD
Compressor	Type	ROTARY	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity / Heating Capacity	BTU/Hr	11800	17750	18300	23040
Rated Cooling Capacity / Heating Capacity	Watts	3457	5200	5362	6750
Rated Power Cooling Input / Heating	Watts	1050	1625	1630	2110
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.29	3.20	3.29	3.20
Current Drawn Cooling / Heating	Amps	4.7	7.2	7.2	9.4
Fan Speed	Steps	3	3	3	3
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	425	425	545	636
Sound Level* (IDU) Cooling / Heating	dB	36	37	37	40
Dimension (IDU) (W X H X D)	mm	798 X 295 X 239	798 X 295 X 239	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	9.5	9.5	12.9	12.9
Net Weight (ODU)	Kg	30.0	37	37.0	46.3
Remocon	Type	Wireless	Wireless	Wireless	Wireless
Connecting Kit	inch	1/2" & 1/4"	5/8" & 1/4"	1/2" & 1/4"	5/8" & 1/4"

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.