

TECHNICAL SPECIFICATIONS

LOGICCOOL 5300f

DESCRIPTION	UNIT	1.0TR	1.5TR	2.0TR
TONNAGE CLASS				
Star Rating	No of BEE Stars	5	5	3
Unit	Model Number	RAU514EUDA	RAU518EUDA	RAU324EUDA
IDU	Model Number	RAS514EUDA	RAS518EUDA	RAS324EUDA
ODU	Model Number	RAC514EUDA	RAC518EUDA	RAC324EUDA
Compressor	Type	ROTARY	ROTARY	ROTARY
Refrigerant	Type	R-410A	R-410A	R-410A
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	13819	19450	23960
Rated Cooling Capacity	Watts	4050	5700	7020
Rated Power Input	Watts	1065	1500	2134
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.80	3.80	3.29
Current Drawn	Amps	4.8	6.7	9.5
Fan Speed	Steps	5	5	5
Air Flow (IDU) (Cooling -Super High)	CFM	424	582.692055	635.66406
Sound Level* (IDU)	dB	40	34	40
Dimension (IDU) (W X H X D)	mm	830 X 290 X 220	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	792 X 600 X 299	792 X 600 X 299
Net Weight (IDU)	Kg	10	12.9	12.9
Net Weight (ODU)	Kg	37.2	45	48.1
Remocon	Type	Wireless	Wireless	Wireless

Features may vary from model to model, some of the models may not be available at all Hitachi outlets. *At Super silent fan speed & at a distance of 1mtr., Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. T&C Apply: Products shown in catalogue are for representation purpose only. Due to continuous research and development, specifications, features and model colour may change without any prior notice.