

TECHNICAL SPECIFICATIONS		Kashikoi 5200i		
DESCRIPTION	UNIT			
Tonnage Class		1.0TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	5	5
Unit	Model Number	RAU512AWEA	RSB518AAEA	RMB524AAEA
IDU	Model Number	RAS512AWEA	ESB518AAEA	EMB524AAEA
ODU	Model Number	RAC512AWEA	CSB518AAEA	CMB524AAEA
Compressor	Type	Rotary	Rotary	Twin Rotary
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity (100% load)	BTU/Hr	12011	18000	24000
Rated Cooling Capacity (50% load)		6483	9000	12000
Maximum Cooling Capacity		14331	20814	26100
Rated Cooling Capacity (100% load)	Watts	3520	5275	7034
Rated Cooling Capacity (50% load)		1900	2638	3517
Maximum Cooling Capacity		4200	6100	7650
Rated Power Input (100% load)	Watts	940	1415	2070
Half Power Input (50% load)		360	495	645
Rated Cooling COP (100% load)	Cooling Capacity (Watts) / Power Input (Watts)	3.74	3.73	3.40
Rated Cooling COP (50% load)		5.28	5.33	5.45
Rated ISEER		4.86	4.85	4.70
Cooling Seasonal Energy Consumption	(kWh)	560	843	1159
Current Drawn (100% load)	Amps	4.3	6.5	9.5
Current Drawn (50% load)		1.8	2.5	3.3
Fan Speed	Steps	5	5	5
Air Flow (IDU) (Cooling - Super High)	CFM	400	583	620
Sound Level* (IDU)	dB	27	33	37
Dimension (IDU) (W X H X D)	mm	798 X 295 X 245	997 X 294 X 258	997 X 294 X 258
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	9.5	13	13
Net Weight (ODU)	Kg	31	35	48
Refrigerant Pipe Diameter	Inches	1/4" X 3/8"	1/4" X 1/2"	1/4" X 5/8"

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52° C.

Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.