

TECHNICAL SPECIFICATIONS		i Connect		
DESCRIPTION	UNIT			
Tonnage Class		1.5TR	1.7TR	2.0TR
Star Rating	No of BEE Stars	5	5	5
Unit	Model Number	RAU518MWD	RAU520MWD	RAU524MWD
IDU	Model Number	RAS518MWD	RAS520MWD	RAS524MWD
ODU	Model Number	RAC518MWD	RAC520MWD	RAC524MWD
Compressor	Type	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity / Heating Capacity	BTU/Hr	18800	19500	24000
Rated Cooling Capacity / Heating Capacity	Watts	5500	5700	7030
Rated Power Cooling Input / Heating	Watts	1485	1425	1950
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.70	4.00	3.61
Current Drawn Cooling / Heating	Amps	6.6	6.4	8.6
Fan Speed	Steps	5	5	5
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	600	600	670
Sound Level* (IDU) Cooling / Heating	dB	33	33	37
Dimension (IDU) (W X H X D)	mm	997 X 294 X 258	997 X 294 X 258	997 X 294 X 258
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	792 X 600 X 299	792 X 600 X 299
Net Weight (IDU)	Kg	13	13	13.9
Net Weight (ODU)	Kg	41.0	43.6	48.1
Remocon	Type	Wireless	Wireless	Wireless
Connecting Kit	inch	5/8" & 1/4"	5/8" & 1/4"	5/8" & 1/4"

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research & development, specifications & features may change without prior notice.