

TECHNICAL SPECIFICATIONS		Neo 5200f		
DESCRIPTION	UNIT			
Tonnage Class		1.2TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	5	4
Unit	Model Number	RAU514HWDD	RAU518HWDD	RAU423HWDD
IDU	Model Number	RAS514HWDD	RAS518HWDD	RAS423HWDD
ODU	Model Number	RAC514HWDD	RAC518HWDD	RAC423HWDD
Compressor	Type	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity / Heating Capacity	BTU/Hr	13819	18800	23200
Rated Cooling Capacity / Heating Capacity	Watts	4050	5500	6800
Rated Power Cooling Input / Heating	Watts	1065	1485	2000
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.80	3.70	3.40
Current Drawn Cooling / Heating	Amps	4.8	6.5	8.7
Fan Speed	Steps	5	5	5
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	424	583	636
Sound Level* (IDU) Cooling / Heating	dB	38	34	37
Dimension (IDU) (W X H X D)	mm	830 X 290 X 220	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	10	12.9	12.9
Net Weight (ODU)	Kg	38.2	41.0	48.1
Remocon	Type	Wireless	Wireless	Wireless
Connecting Kit	inch	1/2" & 1/4"	5/8" & 1/4"	5/8" & 1/4"

Features may vary from model to model. \*At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.