

| TECHNICAL SPECIFICATIONS | | Toushi 3200f | | | |
|---|--|-----------------|-----------------|------------------|------------------|
| DESCRIPTION | UNIT | | | | |
| Tonnage Class | | 1.0TR | 1.5TR | 1.5TR | 2.0TR |
| Star Rating | No of BEE Stars | 3 | 3 | 3 | 3 |
| Unit | Model Number | RAU312KWD | RAU317KWD | RAU318KWD | RAU323KWD |
| IDU | Model Number | RAS312KWD | RAS317KWD | RAS318KWD | RAS323KWD |
| ODU | Model Number | RAC312KWD | RAC317KWD | RAC318KWD | RAC323KWD |
| Compressor | Type | ROTARY | ROTARY | ROTARY | ROTARY |
| Rated Power Supply | Volts/Hz/Phase | 230/50/1 | 230/50/1 | 230/50/1 | 230/50/1 |
| Rated Cooling Capacity / Heating Capacity | BTU/Hr | 11800 | 17750 | 18300 | 23040 |
| Rated Cooling Capacity / Heating Capacity | Watts | 3457 | 5200 | 5362 | 6750 |
| Rated Power Cooling Input / Heating | Watts | 1050 | 1625 | 1630 | 2110 |
| EER | Rated Cooling Capacity (Watts) / Power Input (Watts) | 3.29 | 3.20 | 3.29 | 3.20 |
| Current Drawn Cooling / Heating | Amps | 4.7 | 7.2 | 7.2 | 9.4 |
| Fan Speed | Steps | 3 | 3 | 3 | 3 |
| Air Flow (IDU) (Cooling - Super High) Cooling / Heating | CFM | 425 | 425 | 545 | 636 |
| Sound Level* (IDU) Cooling / Heating | dB | 36 | 37 | 37 | 40 |
| Dimension (IDU) (W X H X D) | mm | 798 X 295 X 239 | 798 X 295 X 239 | 1050 X 290 X 220 | 1050 X 290 X 220 |
| Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| Net Weight (IDU) | Kg | 9.5 | 9.5 | 12.9 | 12.9 |
| Net Weight (ODU) | Kg | 30.0 | 37 | 37.0 | 46.3 |
| Remocon | Type | Wireless | Wireless | Wireless | Wireless |
| Connecting Kit | inch | 1/2" & 1/4" | 5/8" & 1/4" | 1/2" & 1/4" | 5/8" & 1/4" |

Features may vary from model to model. *At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research & development, specifications & features may change without prior notice. The product and remote image is only for representation. It might vary tonnage wise.