

TECHNICAL SPECIFICATIONS		Star Sumo	
DESCRIPTION	UNIT		
<b>Tonnage Class</b>		<b>2.5TR</b>	<b>3.25TR</b>
Star Rating	No of BEE Stars	2	*NA
Unit	Model Number	RAU230HUD	RAU390HUD
IDU	Model Number	RAS230HUD	RAS390HUD
ODU	Model Number	RAC230HUD	RAC390HUD
Compressor	Type	ROTARY	TWIN ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	400/50/3
Rated Cooling Capacity / Heating Capacity	BTU/Hr	29770	39000
Rated Cooling Capacity / Heating Capacity	Watts	8725	11430
Rated Power Cooling Input / Heating	Watts	2825	4200
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.09	2.72
Current Drawn Cooling / Heating	Amps	12.5	7.5/Phase
Fan Speed	Steps	5	3
Air Flow (IDU) (Cooling - Super High) Cooling / Heating	CFM	740	740
Sound Level* (IDU) Cooling / Heating	dB	40	45
Dimension (IDU) (W X H X D)	mm	1150 X 333 X 245	1150 X 333 X 245
Dimension (ODU) (W X H X D)	mm	950 X 740 X 460	950 X 740 X 460
Net Weight (IDU)	Kg	16	16
Net Weight (ODU)	Kg	75.0	84.5
Remocon	Type	LCD	LCD
Connecting Kit	inch	3/4" & 3/8"	3/4" & 3/8"

Features may vary from model to model. \*At Super Silent fan speed & at a distance of 1 m. Hitachi air-conditioners are designed to work in ambient temperatures upto 52° C. Due to continuous research & development, specifications & features may change without prior notice. #BEE does not cover testing of these models.