

TECHNICAL SPECIFICATIONS		KAZE PLUS					
DESCRIPTION	UNIT						
Tonnage Class		1.0TR	1.0TR	1.5TR	1.5TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	3	5	3	2	2
Unit	Model Number	RAW511KUD	RAW312KWD	RAW518KUDZ1	RAW318KUD	RAW218KUD	RAW222KUD
Compressor	Type	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	11942	12000	18000	17402	17402	21019
Rated Cooling Capacity	Watts	3500	3516	5275	5100	5100	6160
Rated Power Input	Watts	1030	1190	1575	1650	1785	2240
EER	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.40	2.95	3.35	3.09	2.86	2.75
Current Drawn	Amps	4.6	5.3	7.0	7.3	8.0	9.9
Fan Speed	Steps	3	3	3	3	3	3
Air Flow (Super High)	CFM	400	300	450	450	450	470
Sound Level*	dB	50	50	50	50	50	52
Dimension (W X H X D)	mm	660 X 430 X 755	560 X 377 X 615	660 X 430 X 755	660 X 430 X 755	660 X 430 X 755	660 X 430 X 755
Net Weight	Kg	52	43	63	61	61	64
Remocon	Type	Wireless	Wireless	Wireless	Wireless	Wireless	Wireless

Features may vary from model to model. Some of the models may not be available at all Hitachi outlets. \*At Super silent fan speed & at a distance of 1m, Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research and development, specifications, features and model colour may change without any prior notice.