

TECHNICAL SPECIFICATIONS		KASHIKOI 5400X		
DESCRIPTION	UNIT			
Tonnage Class		1.0TR	1.5TR	2.0TR
Star Rating	No of BEE Stars	5	5	5
Unit	Model Number	CSA512CBEA	RSA518CBEA	RMA524CBEA
IDU	Model Number	ESA512CBEA	ESA518CBEA	EMA524C BEA
ODU	Model Number	CSA512CBEA	CSA518CBEA	CMA524C BEA
Compressor	Type	Rotary	Rotary	Twin Rotary
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Rated Cooling Capacity	BTU/Hr	12000	18000	24000
Maximum Cooling Capacity		13210	19800	26100
Rated Cooling Capacity	Watts	3520	5275	7034
Maximum Cooling Capacity		3870	5800	7650
Rated Power Input	Watts	800	1420	2070
ISEER		5.75	5.00	4.70
Cooling Seasonal Energy Consumption	(kWh)	474	816	1159
Current Drawn (Rated)	Amps	3.7	6.5	9.5
Fan Speed	Steps	5	5	5
Air Flow (IDU) (Cooling -Super High)	CFM	460	583	620
Sound Level* (IDU)	dB	27	31	37
Dimension (IDU) (W X H X D)	mm	997x294x294	997x294x294	997x294x294
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	750 X 548 X 288	792 X 600 X 299
Net Weight (IDU)	Kg	14	14	14
Net Weight (ODU)	Kg	32	34	48
Refrigerant Pipe Diameter	Inches	1/4" X 3/8"	1/4" X 1/2"	1/4" X 5/8"
Maximum Piping length	Mtr	25	25	25

Features may vary from model to model. \*At Super Silent fan speed & at a distance of 1 m . Hitachi air-conditioners are designed to work in ambient temperatures upto 52

°C.Due to continuous research & development , specifications & features may change without prior notice.